



# ARMORTOP II OUTDOOR COATING

## PRODUCT DESCRIPTION

Armortop II is a specialized coating system designed for use on virtually any exterior surface. Fully UV-tolerant, easy to apply low-VOC acrylic formula. Can be applied to asphalt or concrete. 2-3 coats are recommended. Comes pre-tinted to a variety of colors (see color chart), or available in neutral tint base for field-tinting. Armortop II is factory-textured to provide a safe, non-slip surface with a non-aggressive, small particle size additive to enhance traction when wet, while still being able to be easily cleaned and not 'gritty'. Ideal for sports courts such as tennis and pickleball, plazas, walkways, balconies, porches, patios, pool areas and most any exterior surface. 2-3 coats are recommended depending on surface porosity and texture.

## CHEMICAL AND PHYSICAL ANALYSIS

RESIN	100% ACRYLIC EMULSION
ODOR	SLIGHT AMMONIA
WEIGHT PER 5 GALLON PAIL	APPX. 57-60 LBS
FLAMMABILITY	NONE
FLASH POINT	NONE

## USES

Armortop II is a specialized exterior 100% acrylic emulsion coating designed for tennis courts and other sport and recreational pavement surfaces. coating for balconies, sports courts, porches, patios, and pool decks.

## COMPOSITION

100% acrylic water based emulsion coating

## PACKAGING

Sold in 5 Gal pre-tinted pails

## COLOR

Gray, Blue, Red, Burgundy, Light Brown, Brown, Light green, Meidum Green, Dark Green

# INSTRUCTIONS

**PLEASE READ INSTRUCTIONS THOROUGHLY BEFORE APPLICATION BEGINS. FAILURE TO DO SO CAN RESULT IN PRODUCT FAILURE.**

## PREPARATION

Pavement surface must be cleaned entirely of dust, dirt, debris and all loose materials. Repair of pavement surface defects, depressions and cracks must be completed prior to application. All repairs must be flush and smooth to adjoining surfaces. New asphalt surfaces must cure 14 to 30 days prior to application. New concrete surfaces must cure 28 days prior to application. Concrete surfaces should have a medium broom finish or similar roughened texture. They must never be steel trowelled. Etch surface with Muriatic or Phosphoric Acid and power wash.

## MIXING

Armortop II is ready to use once opened. Stir contents of 5 gallon pail for appx 5 minutes. Ensure that the product consistency looks like a slurry before application. This is an indication that all of the aggregate that feel to the bottom is now mixed. Uneven mixing can lead to flooring failure and uneven texture. Ensure to use a power drill and paddle mixer/metal mixer to mix.

## APPLICATION

Apply mixed coating with a soft rubber squeegee. A minimum of two coats are recommended. Allow each coat to thoroughly dry before applying the next coat. Allow 30-60 minutes before recoating. Wait 48 Hours before allowing foot traffic and heavy equipment to be brought back onto the floor.

## COVERGAE RATES

Each Gal will yield appx. 60-70 SF or 350 SF per pail per coat. Please note coverage will vary depending on surface porosity and application method. Extremely porous substrates will result in reduced coverage rates.

## WARRANTY AND DISCLAIMER

We warrant that our products are manufactured to strict quality assurance specifications and that the information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. Any use or application other than recommended herein is the sole responsibility of the user. Listed physical properties are typical and should not be construed as specifications. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT. We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Our products contain chemicals that may CAUSE SERIOUS PHYSICAL INJURY. BEFORE USING, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.